



Contents lists available at [Curevita Journals](https://Curevita.org)
CUREVITA INNOVATION OF BIODATA INTELLIGENCE
 A Peer-Reviewed International Journal
 journal homepage: www.curevitajournals.com




Adaptive Fusion-Driven Hybrid Deep Learning Model with XAI for Multi-Level Feature Learning in Anemia Detection

^{1,2}Shreya Sharma and ³Ritu Rani

Abstract

Examining Peripheral Blood Smear (PBS) images under a microscope remains the gold standard for diagnosing different types of anemia and evaluating Red Blood Cell (RBC) shape and size. However, manual checks are time-consuming and often depend heavily on the individual technician's experience. To address this, we developed a hybrid deep learning model enhanced with Explainable Artificial Intelligence (XAI) to analyze PBS images automatically. Our system uses a dual-path design—combining Convolutional Neural Networks (CNNs) for fine visual details like texture and edge shape with Vision Transformers (ViTs) for broader contextual information across the image. An adaptive attention mechanism then intelligently blends these two views. To make the system's decisions clear to doctors, we integrated visual tools like Integrated Gradients and Grad-CAM. Tested on benchmark datasets, our model accurately identifies diverse types of anemia and abnormal RBC shapes, offering high diagnostic precision and transparent reasoning.

Infographic abstract



Keywords: Anemia Detection, Peripheral Blood Smear (PBS), Hybrid Deep Learning, Multi-Level Feature Fusion, Explainable AI (XAI), Morphological Analysis.

Article info

Article history: Received 2nd Sep 2026, Revised 18 Sep 2026, Accepted 24th Sept 2026, Published: Sep 2026

Citation: Shreya Sharma and Ritu Rani. 2026. Adaptive Fusion-Driven Hybrid Deep Learning Model with XAI for Multi-Level Feature Learning in Anemia Detection. Curevita Innovation of BioData Intelligence. 2, 3.26-35.

Corresponding Author's Info:^{1,2}Shreya Sharma, ^{1,3}Assistant Professor, Department of Computer Science and Engineering, Galgotias College of Engineering and Technology, Greater Noida, India. ³Ritu²Research Scholar, Department of Computer Science and Engineering, Maharishi Markandeshwar (Deemed to be University), Mullana, India. Email Id: Shreyasharma99964@gmail.com

Publisher: Curevita Research Pvt Ltd

© 2025 Author(s), under CC License; use and share with proper citation.

Introduction

Anemia affects over 1.62 billion people worldwide. While doctors rely heavily on Complete Blood Count (CBC) tests, looking directly at blood samples under a microscope via Peripheral Blood Smear (PBS) images provides crucial visual clues. Observing RBC shapes helps differentiate between microcytic, normocytic, and macrocytic anemia, while spotting specific deformities—like sickle cells, target cells, or teardrop shapes—helps pinpoint exact conditions. Standard deep learning tools have made automatic blood cell analysis easier, but single-path neural networks often struggle to catch both fine edge details of individual cells and broader pattern relationships across a full microscopic field simultaneously. On top of that, many deep learning models operate like "black boxes," making doctors reluctant to rely on them without clear explanations. This paper tackles these challenges directly (Research Objective 03: Design & Implement hybrid models for anemia detection and RBC morphological analysis from PBS images). The core contributions of this work include:

1. A hybrid dual-path network that blends CNNs (for sharp local detail) and Vision Transformers (for global structural context).
2. An Adaptive Feature Fusion Module (AFFM) that uses dynamic attention to weigh fine and broad visual details effectively.
3. Built-in Explainable AI (XAI) tools that highlight specific visual markers, giving clinicians clear and verifiable diagnostic feedback.

2. Methodology

2.1 System Architecture

Our approach runs through three simple stages: clean and isolate the cells, extract features through two complementary neural paths, and intelligently combine those features for final classification.

2.2 Preprocessing and Cell Isolation

To handle differences in lighting and dye colors across lab samples, we first normalize the stain colors in each image. We then use adaptive thresholding and watershed segmentation to isolate individual RBCs and small cell groups, making it

easier to examine their boundaries and shapes.

2.3 Dual-Stream Feature Extraction

Local Detail Path (CNN Branch): A modified EfficientNet focuses on fine spatial details—such as cell borders, central pale regions, membrane roughness, and internal structures.

Global Context Path (ViT Branch): A Vision Transformer analyzes wider patches across the image, mapping out how individual cells relate to one another within the full sample.

2.4 Explainable AI (XAI) Integration

To earn clinical trust, we included two visual explanation tools:

Grad-CAM: Generates color heatmaps over the image to show exactly which parts of a cell—like pale centers or distorted edges—influenced the model's decision.

Integrated Gradients: Checks pixel-level relevance to confirm the model is focusing on genuine cellular structures rather than background noise or staining spots.

1. Architectural Synthesis and Methodological Advances

The core architectural innovation lies in the synergy between two complementary neural paradigms: Convolutional Neural Networks (CNNs) and Vision Transformers (ViTs). Convolutional layers operate as local feature extractors, exceptionally suited for capturing fine-grained cytological markers including cell membrane curvature, central pallor geometry, inclusions, and fine cytoplasmic textures. However, standard CNNs often struggle with capturing long-range spatial dependencies across an entire microscopic field of view. Conversely, Vision Transformers leverage self-attention mechanisms to model macro-level spatial topologies and relationships between adjacent cells, though they can overlook local pixel-level boundary subtleties when applied independently.

To bridge this gap, the integration of an Adaptive Feature Fusion Module (AFFM) dynamically balances local and global feature weights based on spatial variance and information entropy. Rather than relying on simple feature concatenation or late-stage averaging, the AFFM uses learned

attention maps to continuously recalculate the contribution of each stream. This ensures that high-entropy cellular anomalies—such as severe membrane distortion or irregular pallor expansion—are neither masked during feature aggregation nor diluted by background cellular noise.

2. Experimental Validation and Diagnostic Performance

Empirical evaluation on benchmark PBS datasets demonstrated that the proposed model achieves an impressive classification accuracy of 97.6%, with corresponding precision, sensitivity, and specificity metrics reaching 97.3%, 97.5%, and 98.1%, respectively. This performance substantially outpaces traditional baseline architectures, including ResNet-50 (89.2%), standalone Vision Transformers (91.4%), and naive CNN-ViT feature concatenation models (94.1%).

The primary driver behind this significant performance boost is the model's ability to concurrently process micro-level RBC morphology alongside macro-level field characteristics. In traditional

automated workflows, subtle diagnostic indicators—such as mild anisocytosis or early-stage poikilocytosis—often lead to false negatives due to poor local resolution. The proposed framework preserves granular structural data across all hidden layers, allowing the classification heads to differentiate between closely related sub-types of anemia (e.g., microcytic hypochromic anemia versus iron deficiency states) with high statistical confidence.

3. Explainability, Interpretability, and Clinical Trust

Beyond quantitative accuracy, incorporating Explainable AI (XAI) frameworks—specifically Gradient-Weighted Class Activation Mapping (Grad-CAM) and Integrated Gradients—ensures necessary diagnostic transparency for clinical adoption. Deep learning systems have historically faced resistance in clinical environments due to their "black-box" nature. Medical professionals require verifiable rationale before acting on automated diagnostic recommendations.

The visual attributions produced by our integrated XAI pipeline confirm

that the network bases its predictions directly on clinically validated hematological markers:

Central Pallor Regions: Visual heatmaps explicitly highlight expanded central pallor zones during the classification of microcytic hypochromic anemia, aligning perfectly with standard diagnostic protocols.

Membrane Geometry and Shape Deformities: Pixel-level attribution maps concentrate along abnormal edge curvatures when identifying abnormal morphotypes, such as drepanocytes (sickle cells), dacrocytes (teardrop cells), and codocytes (target cells).

Artifact Rejection: Gradient verification confirms that the model ignores background staining artifacts, debris, and overlapped non-diagnostic cellular clusters, focusing strictly on viable cell morphology.

By providing clear visual justifications alongside numerical confidence scores, the framework functions as a collaborative "second reader" for hematologists, reducing diagnostic

fatigue while maintaining high interpretability.

4. Operational Impact and Future Directions

The proposed hybrid framework offers a scalable, objective, and interpretable decision-support platform tailored for modern pathology workflows. By automating the labor-intensive aspects of microscopic slide scoring, this framework provides a practical pathway toward rapid, high-throughput screening for diverse anemia subtypes and associated blood disorders.

Key operational benefits include:

Reduced Turnaround Time: Automates preliminary cell scoring and classification within seconds, expediting critical laboratory reporting.

Standardization: Minimizes diagnostic subjectivity and variability across different

laboratories, operators, and staining protocols.

Resource Optimization: Enables pathology labs in low-resource

settings to conduct automated initial triage, reserving specialist review for complex or borderline cases.

Looking forward, future extensions of this research will focus on optimizing model parameters for low-latency edge deployment directly onto automated microscope platforms. Additionally, expanding the multi-task learning capabilities of the network to simultaneously detect concurrent hematological conditions—such as parasitic infections (e.g., malaria) or white blood cell abnormalities alongside RBC malformations—will further enhance its real-world diagnostic utility.

This study demonstrates that combining local CNN feature detection with global Transformer context creates a robust, highly accurate tool for automated anemia detection. Adding dynamic fusion and

visual XAI heatmaps makes the model both precise and transparent for practical medical settings. Our next step is optimizing this system so it can run directly on automated laboratory microscopes in real time.

3. Results and Discussion

3.1 Experimental Setup

We built the framework using PyTorch and evaluated it on benchmark PBS image datasets containing normal cells alongside microcytic, macrocytic, and normocytic anemia samples. Data augmentation techniques (such as slight rotations, flipping, and lighting adjustments) were used during training to prevent the model from simply memorizing training images.

3.2 Performance Comparison

The hybrid model outperformed traditional single-stream setups across standard evaluation metrics:

TABLE 1: Quantitative Performance Comparison of Model Architectures for Anemia Classification from PBS Images

Model Architecture	Accuracy (%)	Precision (%)	Sensitivity (%)	Specificity (%)	F1-Score (%)
ResNet-50 (Baseline)	89.2	88.5	89.0	91.1	88.7
Vision Transformer (ViT-B/16)	91.4	91.0	90.8	92.5	90.9
Standard Hybrid (CNN + ViT Concatenation)	94.1	93.8	94.0	95.2	93.9
Proposed Adaptive Fusion Hybrid (with XAI)	97.6	97.3	97.5	98.1	97.4

All results are based on cross-validation on combined benchmark PBS datasets.

3.3 Visual Explanation & Diagnostic Insights

Our adaptive fusion model reached 97.6% accuracy, clearly beating standard single-path networks and basic combination methods. Looking closely at the XAI visual heatmaps confirmed that the model consistently zeros in on key clinical markers:

Central Pale Area: Correctly focuses on enlarged pale centers when

identifying microcytic hypochromic anemia.

Cell Edge Curvature: Accurately highlights distorted boundaries in misshapen cells, such as sickle cells or teardrop shapes.

4. Conclusion

The primary objective of this research was to design, implement, and validate an adaptive fusion-driven hybrid deep learning model enhanced

with Explainable Artificial Intelligence (XAI) for automated anemia classification and Red Blood Cell (RBC) morphological analysis from Peripheral Blood Smear (PBS) images. Manual hematological examination under optical microscopy remains subject to significant inter-observer variability, high turnaround times, and diagnostic fatigue, particularly in high-volume pathology settings. By synthesizing localized spatial feature representation with global contextual modeling, the proposed dual-path architecture resolves the structural trade-offs typical of traditional single-stream deep neural networks.

References

- Ahuja, S., & Singh, P. (2026). Deep learning in public health: Evaluating anemia detection methods and blood cell classification paradigms. *International Journal on Smart Sensing and Intelligent Systems*, 19(1), 101–114.
- Alshehri, O. M., Shaf, A., Irfan, M., Jalal, M. M., & Altayar, M. A. (2025). A hybrid CNN-Transformer framework for normal blood cell classification: Towards automated hematological analysis. *Computer Modeling in Engineering & Sciences*, 144(1), 1165–1196.
- Alom, M. Z., & Taha, T. M. (2024). Explainable Artificial Intelligence (XAI) for medical image analysis: Architectural advances and clinical interpretability in diagnostic imaging. *IEEE Transactions on Medical Imaging*, 43(2), 512–526.
- Alotaibi, N., & Al-Mulla, A. (2024). An explainable AI-based blood cell classification using optimized convolutional neural network with Grad-CAM and SHAP. *Journal of Pathology Informatics*, 15, 100389.
- Bhattacharya, S., & Ghosh, A. (2025). Multi-scale feature extraction in vision transformers for single-cell morphometry. *Pattern Recognition in Medicine*, 88, 109312.
- Chen, X., & Liu, Y. (2023). Automated iron deficiency anemia detection from peripheral blood smear images using fine-tuned deep residual networks. *Computers in Biology and Medicine*, 162, 107085.
- Dhanasekaran, S., & Shanker, N. R. (2023). Anemia detection using a deep learning algorithm by image processing and neural networks. *International Journal on Recent and*

Innovation Trends in Computing and Communication, 11(7s), 79–89.

Gupta, R., Sharma, S., & Kumar, P. (2025). Prediction of hemoglobin levels and red blood cell parameters using multi-center microscopic blood smear datasets. *Innovation and Medicine*, 12(1), 102–115.

Hassan, M., & Rahman, A. (2024). Lightweight Explainable Deep Learning (GRsNet) with Grad-CAM, LIME, and SHAP integration for automated microscopic blood cell classification. *Computer Modeling in Engineering & Sciences*, 145(2), 520–542.

Islam, M. S., & Hossain, M. A. (2023). Deep Learning-powered anemia detection from blood smear images: A comparative evaluation of CNN backbones. *Journal of Digital Imaging*, 36(4), 1612–1625.

Joshi, A., & Patel, V. (2024). Efficient diagnostic model for iron deficiency anemia detection using automated hypochromic microcyte identification from PBS images. *Computer Methods and Programs in Biomedicine*, 248, 108110.

Khan, R., & Ahmed, Z. (2025). Attention-guided feature fusion in hybrid deep networks for biomedical

image analysis. *IEEE Signal Processing Letters*, 32, 411–415.

Kumar, S., & Verma, N. (2024). Stain normalization and adaptive segmentation techniques for peripheral blood smear microscopy. *Microscopy Research and Technique*, 87(5), 982–996.

Li, X., Wang, Y., & Zhang, H. (2024). A lightweight explainable deep learning model with Grad-CAM integration for automated microscopic blood cell classification. *Computer Methods and Programs in Biomedicine*, 245, 108012.

Mehta, P., & Shah, D. (2025). Deep learning approaches for red blood cell morphology analysis in sickle cell disease and related hemoglobinopathies. *Blood Cells, Molecules, and Diseases*, 110, 102801.

Nath, S., & Roy, K. (2023). Automated RBC morphological analysis and classification using hybrid spatial-channel attention mechanisms. *Biomedical Signal Processing and Control*, 85, 104880.

Patel, K., & Sundaram, M. (2026). Dual-stream vision transformer architectures for microscopic hematology: Benchmarks and clinical

- feasibility. *Journal of Medical Systems*, 50(2), 114–128.
- Ravi, V. R., & Akalin, F. (2024). Comparative performance evaluation of deep convolutional architectures for non-invasive hematological screening. *Journal of AI-Driven Healthcare Systems*, 8(3), 145–158.
- Reddy, P., & Rao, K. V. (2025). Explainable AI mechanisms in digital pathology: Bridging the trust gap between deep learning and hematologists. *Artificial Intelligence in Healthcare*, 14(1), 45–62.
- Sarma, B., & Das, H. (2024). High-throughput RBC segmentation and pallor area ratio estimation using dynamic thresholding and deep learning. *IEEE Transactions on Biomedical Engineering*, 71(8), 2410–2421.
- Sharma, A., & Malhotra, R. (2023). Evaluation of vision transformers versus convolutional networks in single-cell microscopic diagnostics. *Expert Systems with Applications*, 225, 120110.
- Singh, M., & Bansal, P. (2025). Dual-branch hybrid neural networks for cellular classification in digital microscopic images. *Neural Computing and Applications*, 37(6), 3120–3135.
- Srivastava, A., & Mittal, M. (2025). Aligning deep learning and interpretable explainer models for peripheral blood smear examination and cell morphology segmentation. *Artificial Intelligence in Medicine*, 158, 102890.
- Takahashi, M., & Sato, Y. (2024). Quantitative morphology profiling of red blood cells using spatial self-attention networks. *Medical Image Analysis*, 91, 103015.
- Vasquez, D., & Chen, L. (2025). Unstained and stained blood smear analysis: A review of rule-based, machine learning, and hybrid deep learning approaches. *Biophotonics and Clinical Diagnostics*, 19(2), 211–228.
- Verma, R., & Agarwal, S. (2023). Deep learning-based automated counting and classification of microcytes, macrocytes, and poikilocytes in PBS images. *Diagnostics*, 13(12), 2045.